



Sound and thermal insulation

CEILING PANELS



THERMAL
INSULATION



SOUND
INSULATION



QUICK & EASY
INSTALLATION



BASED ON 100 %
NATURAL WOODFIBRE



FORMALDEHYDE
FREE



RECYCLABLE



ISOTEX ceiling panels are soft board based products with decorative paper covering. ISOTEX is alternative decoration material to hardboard based panels to get more advantages.



Ceiling panels Quatro have tongue and groove joints in all four edges



Ceiling panels Quatro

Thickness	mm	12 ± 1
Width	mm	300 ± 2
Length	mm	1800±2
Density	kg/m ³	> 230
Package	pcs	8
Package area	m ²	4,32
On a pallet	packages	30
Pallet area	m ²	129,6
Pallets weight	kg br net	473 420
Pallets length	mm	1810
Pallets width	mm	1000
Pallets height	mm	1100



Installation of ceiling panels

Installation on a wooden frame:


When constructing the wooden frame, you should use wooden rafters with a size of 19 x 44 mm. Fix the rafters so that the distance between them (measured from the centre of each rafter) is 300 mm. Fix the panels on the frame using staples (the length of which should be 10–14 mm), making sure that the distance between the staples is no greater than 100 mm. The outermost panel is to be fixed on the frame with nails, screws or adhesive so that the mould installed later would cover them. The panels are always fixed along the framework of rafters. Even better results are achieved when the gaps between the longer edges of the panels are fixed in the direction of the falling light.

Installation with adhesive:

Apply a strip of adhesive on the back side of a panel, approximately 30 mm from the edge of the panel, and apply dots of adhesive to the centre of the panel, approximately one dot after every 200 mm. Press the panel to the ceiling so that it is a slight distance away from the previous panel. Slide the panel sideways to level the adhesive and fix the tongue into the groove. If at all possible, the panels can be fixed with staples to provide additional support.

Attention! Always follow the instructions provided by the manufacturer of the adhesive.

Properly installed ISOTEX ceiling panels are durable. No cracks will appear on the surface of the panels – one of the most common “beauty flaws” of ceilings and walls made of other materials. Additional information and an installation video on ISOTEX panels can be found on the web site www.isotex.ee



AS VIISNURK

www.isoplaat.eu
Made in EU



Trgovina PTK, Tilen Kokelj, s.p., Miševa ulica 8, 1230 Domžale
Tel.: +386 (0)41 305 777, info@ptk.si, www.ptk.si